


Multiband 4-in-1 Dome Omni Antenna

4-Port 617-6000MHz, SMA Male



- ❖ Multiband 4-in-1 Dome Omnidirectional Antenna with SMA Male leads
- ❖ 4x4 Ultra-wideband (617-6000MHz) to support MIMO/diversity at 4G/5G
- ❖ Indoor and Outdoor rated IP69K design with UV stabilized radome

Compatible with most 4G/5G enabled gateways









Connector Option	Product SKU	Ventev Part #
SMA Male Leads	279935	VM-UW4OD-SM

For more information or to purchase, contact Ventev: 800.851.4965 or sales@ventev.com

Electrical Specifications				
Cable Leads Number	Cable 1 to 4 (4G/5G Elements)			
Frequency Bands, MHz	617–6000			
Gain, dBi	617-960 MHz	4 dBi	3300-4200 MHz	7 dBi
	1690-2700 MHz	6 dBi	4900-6000 MHz	8 dBi
Polarization	Vertical			
Azimuth (HBW)	Omni (360°)			
Isolation, dBm	> 10			
VSWR	≤ 2.0			
Impedance, ohm	50			
Mechanical Specifications				
Product Dims (Dia x H)	Ø175 x 80 mm (Ø7.0 x 3.15 in)			
Input Connector / Pigtail	Cellular Cables (leads #1 to 4) : SMA Male; 17ft Pigtail w/ RG58			
Radome	UV Stabilized ABS. White (Black color option available with 25unit MOQ; Contact Ventev Sales)			
Operating Temperature	-40° C to +80° C (-40° F to +176° F)			
Ingress Protection	IP69K			
Mounting	Through 1.0” hole using stainless Nut; Silicone O-ring included; Adhesive backed sealing pad on the back to minimize shaking			
Application	Indoor or Outdoor			
Product Weight	1.2Kq (2.6 lbs)			









Multiband 4-in-1 Dome Omni Antenna

4-Port 617-6000MHz, SMA Male

Frequency	E Plane	H Plane
700 MHz		
800 MHz		
900 MHz		
1700 MHz		









Multiband 4-in-1 Dome Omni Antenna

4-Port 617-6000MHz, SMA Male

Frequency	E Plane	H Plane
2200 MHz		
2400 MHz		
2600 MHz		
3300 MHz		

Multiband 4-in-1 Dome Omni Antenna

4-Port 617-6000MHz, SMA Male

Frequency	E Plane	H Plane
3600 MHz		
4200 MHz		
4900 MHz		
5500 MHz		
6000 MHz	