ventev

2.4/5 Ghz 4/6 dBi Wi-Fi Mini Omni Antenna with 4 RA RPSMA Male Connectors

Ventev's 2.4/5 GHz 4/6 dBi small form factor ceiling mount multiple-input and multiple-output (MIMO) omnidirectional Wi-Fi antenna is designed to be operated with any manufacturer's latest 802.11ac Waves II WLAN access points. The antenna's appealing design maintains building decor while providing outstanding Wi-Fi connectivity. The 4 dual-band leads with rightangle connectors deliver exceptional performance while simplifying connection to the access point. Features a threaded plastic bushing and nut for simple ceiling tile mounting. *Every Ventev antenna is RoHS compliant and covered by Ventev's two-year TerraNet warranty program.*

For more information or to purchase, contact Ventev: 800.851.4965 or sales@ventev.com.


SPECIFICATIONS

Sku	295094
Model Number	M6040060O2D1802RS
Frequency Range	2.4/5 GHz
Gain	4/6 dBi
Vertical Beamwidth	60°/ 70°
Horizontal Beamwidth	360°
Polarization	Vertical
Environment	Indoor
VSWR	≤ 2.0/ ≤ 2.5
Maximum Input Power	2 W
Mounting Method	Center Thread Screw
Number of Ports/Cable	4
Connector Type	RA RPSMA Male
Dimensions	5.4 x 2.9 x 1"
Weight	.44 lbs.
Radome Color and Material	White
Operating Temperature	-40°F to 158°F




Radiation Patterns

Vertical Radiation at 2.4 GHz



Vertical Radiation at 5 GHz



Terrawave by Ventev



2.4/5 Ghz 4/6 dBi Wi-Fi Mini Omni Antenna with 4 RA RPSMA Male Connectors

Mounting Information









Terrawave by Ventev