

Global IFS® TecCrete® 1250 Raised Access Floor Wi-Fi Omni Antenna with 4 RPSMA Connectors





SPECIFICATIONS

SKU: 298232

Model Number: M6030030042420TA

Frequency Range: 2.4-2.5/5.150-5.850 GHz

Gain: 3/6 dBi

Vertical Beamwidth: 55° / 40°

Polarization: Verical

VSWR: </= 2.5 dBi

Maximum Input Power: 10W

Ports: 4

Connector Type: RPSMA Male

Antenna Cable: 36" Plenum

Dimensions: 1.378" x 9" x 0.11"

Weight: 42 lbs.


Mounting Method(s): Atop Raised Access Flooring Pedestals


Operating Temperature: 0°F to 140°F

Ventev's patent-pending TerraWave Raised Access Floor Wi-Fi Antenna embeds Ventev's proprietary antenna technology into Global IFS® TecCrete® Access Flooring 1250 panels. The Access Floor Antenna is typically deployed in raised-floor environments, such as offices, schools, libraries, museums and casinos, where aesthetics and an open environment matter. Deployed under a variety of fabrics and finishes, this antenna will withstand normal office activities, including proper load bearing, with no performance degradation.

For more information or to purchase, contact Ventev: 800.851.4965 or sales@ventev.com.

RADIATION PATTERNS





5 GHz

sales@ventev.com