



- NOTE:
1. Impedance: 50Ω
 2. Frequency Range: DC 0-11 GHz
 3. V.S.W.R. : ≤ 1.3
 4. Voltage Rating: 1500V rms
 5. Contact Resistance: Center Contacts: 1.0 mΩ Max
Outer Contacts: 0.5 mΩ Max
 6. Insulation Resistance: 5000 MΩ MIN.
 7. Interface in Accordance With: MIL-STD-348A
 8. Operating Temperature Range: -65°~165°C
 9. ROHS Compliance.

					TOLERANCES				TITLE				
					DIMENSIONS ARE IN MILLIMETER				N-Style Plug to N-Style Plug Adapter				
7	CHASSIS	BRASS	NICKEL	1	E-0029	UNLESS OTHERWISE SPECIFIED .X ±0.2 .XX ±0.1 .XXX ±0.05 ANGLES ±5°				PART NO.		APPROVED	DATE
6	CENTER CONTACT	BRASS	GOLD	1	C-0413					NM-NM		CHECKED	DATE
5	INSULATOR	TEFLON	NONE	1	T-0318					DRAWN NO.		DRAWN	DATE
4	BODY	BRASS	NICKEL	1	B-0136					SCALE		FILE PATH:	
3	WASHER	BRASS	NICKEL	2	G-0019					3/1	ISSUE	A-0	
2	GASKET	RUBBER	NONE	2	R-0004								
	SHELL	BRASS	NICKEL	2	A-0009								
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWN NO.								