


- NOTE:
- 1.Impedance: 50Ω
 - 2.Frequency Range: DC 0-11 GHz
 - 3.V.S.W.R.: 1.3 MAX. @ 6GHz
 - 4.Voltage Rating: 1500V rms
 - 5.Contact Resistance: Center Contacts: 1.0 mΩ Max
Outer Contacts: 1.0 mΩ Max
 - 6.Insulation Resistance: 5000 MΩ MIN.
 - 7.Interface in Accordance With: MIL-STD 348A
 - 8.Operating Temperature Range: -65°~165°C
 - 9.ROHS Compliance.



STRIPPING DIMENSION

ISS	ZONE	REVISION		DESCRIPTION	

9	HEAT TUBING	PE	BLACK	1	H-0067	TOLERANCES DIMENSIONS ARE IN MILLIMETER UNLESS OTHERWISE SPECIFIED .X ±0.2 .XX ±0.1 .XXX ±0.05 ANGLES ±5°	TITLE N Plug Straight Crimp for 400 Series Cable			
8	FERRULE	BRASS	WHITE BRONZE	1	M-0275		PART NO. CON-07-400-CP-HEX			APPROVED DATE
7	BODY	BRASS	WHITE BRONZE	1	B-0915		DRAWN NO. 11-0197			CHECKED DATE
6	INSULATOR	TEFLON	NONE	1	T-0592		FILE PATH:		DRAWN DATE	
5	WASHER	BRASS	NONE	1	G-0019					
4	CHASSIS	BRASS	WHITE BRONZE	1	E-0029					
3	GASKET	SILICONE	NONE	1	R-0004					
2	CENTER CONTACT	Be Cu	GOLD	1	C-0758					
1	SHELL	BRASS	WHITE BRONZE	1	A-0083					

F
E
D
C
B
A

F
E
D
C
B
A

1 2 3 4 5 6 7 8