



Recommended Stripping Dimensions

NOTE:
 1.Impedance: 50Ω
 2.Frequency Range: DC 0–18 GHz
 3.V.S.W.R.: 1.3 MAX. @ 6GHz
 4.Voltage Rating: 500V rms
 5.Contact Resistance: Center Contacts: 2.0 mΩ Max
 Outer Contacts: 2.0 mΩ Max
 6.Insulation Resistance : 5000 MΩ MIN.
 7.Operating Temperature Range: -65°~165°C
 8.ROHS Compliance.

REVISION						TOLERANCES				TITLE		TerraWave Solutions	
ISS	ZONE	DESCRIPTION				DIMENSIONS ARE IN MILLIMETER				RPSMA Bulkhead Jack for TWS-240 Cable		APPROVED	
						UNLESS OTHERWISE SPECIFIED				PART NO.		DATE	
7	FERRULE	BRASS	GOLD	1	M-0066	.X	±0.2	DRAWN NO.		CON-30-240		CHECKED	
6	PIN	BRASS	GOLD	1	C-0322	.XX	±0.1	FILE PATH:				DATE	
5	BODY	BRASS	GOLD	1	B-0416	.XXX	±0.05					DRAWN	
4	INSULATOR A	TEFLON	NONE	1	T-0267	ANGLES	±5°					DATE	
3	WASHER	BRASS	GOLD	1	F-0023							DATE	
2	WASHER	BRASS	GOLD	1	G-0017							DATE	
1	NUT	BRASS	GOLD	1	D-0008							DATE	
NO.	DESCRIPTION	MATERIAL	FINISH	Q'TY	DRAWN NO.	SCALE	4/1	ISSUE	A-0				