



- NOTE:
1. Impedance : 50Ω
  2. Frequency Range: DC 0-6 GHz
  3. V.S.W.R. : < 1.3
  4. Voltage Rating: 1000V rms
  5. Contact Resistance: Center Contacts : 1.0 mΩ  
Outer Contacts : 0.5 mΩ
  6. Interface in Accordance With: MIL-STD-348A
  7. Operating Temperature Range: -65°~165°C
  8. RDHS Compliance.

10	NUT	BRASS	NICKEL	1	D-0060
9	CHASSIS	BRASS	NICKEL	1	E-0161
8	BODY	BRASS	NICKEL	1	B-0736
7	WASHER	BRASS	NONE	1	G-0019
6	INSULATION	TEFLON	NONE	1	T-0425
5	GASKET	SILICONE	NONE	1	R-0004
4	CENTER CONTACT	BRASS	GOLD	1	C-0603
3	CHASSIS	BRASS	NICKEL	1	E-0029
2	SHELL	BRASS	NICKEL	1	A-0009
1	FERRULE	BRASS	NICKEL	1	M-0150

TOLERANCES			
DIMENSIONS ARE IN MILLIMETER			
UNLESS OTHERWISE SPECIFIED			
.X	±0.2		
.XX	±0.1		
.XXX	±0.05		
ANGLES	±5°		
SCALE	3/1	ISSUE	A-0

TITLE	Right Angle N-Style Plug for TWS-400 Cable
PART NO.	CON-07RA-400
DRAWN NO.	
FILE PATH:	

TerraWave Solutions	
APPROVED	DATE
CHECKED	DATE
DRAWN	DATE