

24V Integrated UPS Power System, Polycarbonate, SLA Batteries VN-124B1-070-1

By Ventev Catalog # VN-124B1-070-1

Ventev's 24V DC UPS Power System is designed for IoT applications to ensure reliable power for Cellular and SCADA radios. The compact, lightweight NEMA 3R enclosure system converts 120 V AC site power to 24V DC to power active equipment. The system includes sealed lead-acid batteries that provide several hours of back-up in case of power outage. Easily configurable in the field, the system is delivered fully integrated to meet your specific deployment requirements and can be mounted on poles or walls.

Features

- Converts AC power to DC power.
- 24V of battery back-up providing UPS functionality allowing the system to operate several hours without AC power.
- Rugged NEMA-rated enclosure protects in harsh weather.
- The thermostat-controlled fan and vent keep the system cool during the most extreme conditions.
- Latches for padlocks to secure equipment from tampering and theft.
- Pole or wall mountable.
- Configured and delivered fully integrated for fast, trouble-free installation.
- Cost-effective solution for ensuring reliable power for uninterrupted connectivity.

Applications

- Smart Grid: powers collector point systems for LTE backhaul radios with enclosure I/O ports for antenna cables.
- Smart Farming: provides 24V DC to power Gateway radio systems with accommodations for external LTE antennas.
- SCADA Networks: Protects remote equipment and provides 24V DC power to SCADA radio with UPS and integrated antennas.

General

Environment Indoor or Outdoor

Installation Type Wall or pole mount

Color Gray

Additional Accessories TWPMK-16-UNIV: Pole Mount Kit

(sold se parately) RJ-45FT: 1" Diameter Cable Glands

1/2-NEMA-PLUG: 1" Diameter Hole Plug



Specifications

Dimensions 18x16x10 inches

Weight 25 lbs.

Lock Type Padlock-able latches

Material Polycarbonate

Operating Temperature -22 to 113°F

Vents 75 CFM, 24V DC fan

Holes/Ports AC-input (1), RJ45 I/O (1)

NEMA Rating 3R

Input Power 90-264V AC, 60 Hz, 3 A

Output Power 120W at 24V DC

Battery Back-up Sealed lead-acid, auto switchover

System Protections* LVD, Overload, Over Voltage & Temp.

Terminal Blocks AC, DC and Ground w/ knife switches

UPC 662620925042

Product Assets

Sales Drawings – Outline Drawing (link) Specifications – Specifications Sheet (link)



^{*}Note: low voltage disconnect w/ cutoff 10.5V, reconnect 12.5V. Over-voltage autorecovery. Over temperature, auto-recovery after temperature goes below set-point.



24V Integrated UPS Power System, Polycarbonate, SLA Batteries VN-124B1-070-1

By Ventev Catalog # VN-124B1-070-1

