

Div 2/ Zone 2 Wireless Enclosure System for Division 2 & Zone 2 Hazardous Environments

Ventev's Div 2 Wireless Enclosure system for hazardous environments is ideal for Division 2 and Zone 2 areas. The enclosure is fully certified and enables deployment of access points in hazardous areas. This solution is suitable for deployments in indoor or outdoor operations that require stringent regulatory control of potential flames or sparks, and where flammable gases or vapors, dusts and ignitable fibers exist. Ideal for industries such as oil and gas, petrochemical, mining, pharmaceutical, and chemical plants. These enclosures include a wireless access point.

All Included Access Points are Configured for USA Domain.

Specifications

SKU	See Page 2
Cover & Enclosure Materials	Marine grade cufree aluminum alloy, polyester powder coated finish
Ingress Protection	IP66/ NEMA 4X
Power	IEEE 802.3at PoE power (M20 tap at bottom of enclosure for power in. The M20 to 3/4 in. NPT adapter is included for NA deployments)
Mounting	Wall mounting feet included; pole mount kit sold separately
Antenna Port	4x N Female (4x top)
Weight	40 lbs.
External Dimensions	22.84 x 19.69 x 15.74 in.

Certifications

- Ex II 3 (3) G Ex ec [ic Gc] nR IIC T6 Gc
- Ex II 3 (3) D Ex [ic Dc] tc IIIC T85°C Dc
- cMETus Class I, Div 2, Groups A-D
- cMETus Class II, Div 2, Groups F-G
- cMETus Class I, Zone 2 AEx ec ic nR IIC T6 Gc
- cMETus Class II, Zone 22 AEx ec ic tc IIIC T85°C Dc



Features & Benefits

- Fully certified enclosure for Div 2/Zone 2 hazardous area with access point.
- ATEX and IECEx Zone 2 and 22 certified; cMETus Class I, II Division 2 and Zone 2 certified.
- Intrinsically Safe RF outputs allows use of noncertified antennas.
- Tapped hole at bottom of enclosure for PoE Input.
- External grounding lug installed. Internal grounding through metal backplate.
- Simple and quick installation.
- Includes a wireless access point.

**This is fully certified ATEX, IECEx and cMETus enclosure solution with Access Point (AP) integrated. Customer supplies AP (free issue) to Ventev for integration into the enclosure on certified assembly line.*

Ventev's protective enclosures are covered by the company's 1-year warranty.

All product specifications are subject to change without notice or obligation.

Div 2/ Zone 2 Wireless Enclosure System for Division 2 & Zone 2 Hazardous Environments

Available Models

C1 DII Enclosure with Access Point	MFG Part #	SKU	Operating Temperature (°C)	Operating Temperature (°F)
C1 DII Aruba AP534	VNV-C1D2-AP534	230617	0° to +45°C	32°to +113°F
C1 DII Aruba 518	VNV-C1D2-AP518	239458	-40° to +50°C	-40° to +122°F
C1 DII Cisco 9120AXE	VNV-C1D2-9120	223380	-20° to +45°C	-4° to +113°F
C1 DII Cisco 9130AXE	VNV-C1D2-9130	258028	-20° to +45°C	-4° to +113°F
C1 DII Cisco ESW6300	VNV-C1D2-ESW6300	227727	-20° to +60°C	-4° to +140°F
C1 DII Meraki MR76	VNV-C1D2-MR76	241972	-20° to +50°C	-4° to +122°F
C1 DII Meraki MR86	VNV-C1D2-MR86	236671	-20° to +50°C	-4° to +122°F

Ventev's protective enclosures are covered by the company's 1-year warranty.

All product specifications are subject to change without notice or obligation.