

TerraWave® 2.4/5 GHz 2.5/4 dBi Micro Omni Antenna

with 2 RPSMA Male Connectors

Ventev's TerraWave® 2.4/5 GHz 2.5/4 dBi Micro Omnidirectional Wi-Fi Antenna with 2 RPSMA Male connectors is designed to be operated with any manufacturer's 2 and 4 lead 802.11 ac Waves I & II WLAN access points. This small, visually appealing surface mount antenna is an ideal solution for low profile and/or aesthetic deployments. It can also be used in vehicles for communications, location tracking, and fleet management. An L-bracket with U-Bolts (SKU 509824) is included with the antenna for wall or mast mounting.

Specifications

SKU	287214
Manufacturer Part Number	M602504003D220MW
Operating Frequency Range	2.4/5 GHz
Polarization	Vertical
Horizontal Beamwidth	360°
Gain	2.5/4 dBi
VSWR	≤ 2.0
Max Input Power	20 W
Nominal Impedance	50 Ohms
Number of Ports	2
Length of Lead	48 in.
RF Connector	RPSMA Male
Application	Indoor/Outdoor
Operating Temperature	-40° to 158°F
Dimensions	3.54 x 1.57 in.
Weight	0.50 lbs.
Mounting Options	Wall or Mast
Radome	White




All product specifications are subject to change without notice or obligation.


TerraWave[®] 2.4/5 GHz 2.5/4 dBi Micro Omni Antenna

with 2 RPSMA Male Connectors


Radiation Patterns




Port 1
2.4 GHz
E Plane




Port 1
2.4 GHz
H Plane




Port 1
5 GHz
E Plane




Port 1
5 GHz
H Plane




Port 2
2.4 GHz
E Plane



Port 2
2.4 GHz
H Plane



Port 2
5 GHz
E Plane



Port 2
5 GHz
H Plane



All product specifications are
subject to change without notice
or obligation.