## 2.4/5 GHz 6 dBi MIMO Omnidirectional Antenna

with 6 RPSMA Male Connectors




Ventev's 6 dBi outdoor multiple-input and multiple-output (MIMO) omnidirectional antenna is designed to operate enterprise class 802.11n MIMO access points. With dual-band leads, each cable supports both 2.4 and 5 GHz, making it an ideal and aesthetically pleasing antenna to support demanding outdoor applications in next generation IEEE 802.11n wireless communication systems. The rugged enclosure makes this antenna perfectly suited for use in a warehouse or manufacturing environment where it must withstand exposure to moisture and dust. Includes an L-Bracket for mast and or wall mounting. Industrial beam clamps could be purchased as an additional option but are not included.

## **Specifications**

SKU	356602
Model Number	M6060060MO1D3620O
Operating Frequency Range	2.4/5 GHz
Gain	6 dBi
Polarization	Vertical
Vertical Beamwidth	35°/25°
Horizontal Beamwidth	360°
VSWR	≤ 1.5 - 2.0
Nominal Impedance	50 Ohms
Max Input Power	10 W
Number of Ports	6
Length of Lead	36 in.
RF Connector	RPSMA Male
Application	Outdoor
Operating Temperature	-40° to 158°F
Dimensions	5.9 x 7 in.
Weight	3.15 lbs.
Wind Rating	134 mph



## **Radiation Patterns**





All product specifications are subject to change without notice or obligation.